

Model	Kapasite (Nm <sup>3</sup> /dk)	Baęlantı apı	Voltaj (V/Ph/Hz)	Max. alıřma Basıncı	Filtre Modeli
SED 1.2	1,20	3/4"	220/1/50	16 bar	GF1.2 + CF1.2
SED 2.0	2,00	1"	220/1/50	16 bar	GF2.0+CF2.0
SED 2.5	2,50	1"	220/1/50	16 bar	GF2.5+CF2.5
SED 4.0	4,00	1 1/2"	220/1/50	16 bar	GF4.0+CF4.0
SED 6.0	6,00	1 1/2"	220/1/50	16 bar	GD6.0+CF6.0
SED 8.0	8,00	1 1/2"	220/1/50	16 bar	GF8.0+CF8.0
SED 10.0	10,00	2"	380/3/50	16 bar	GF10.0+CF10.0
SED 13.0	13,00	2"	380/3/50	16 bar	GF13.0+CF13.0
SED 18.0	18,00	2 1/2"	380/3/50	16 bar	GF18.0+CF18.0
SED 21.0	21,00	2 1/2"	380/3/50	16 bar	GF21.0+CF21.0
SED 24.0	24,00	3"	380/3/50	16 bar	GF24.0+CF24.0
SED 32.0	32,00	4"	380/3/50	16 bar	GF32.0+CF32.0
SED 44.0	44,00	4"	380/3/50	16 bar	GF44.0+CF44.0
SED 52.0	52,00	4"	380/3/51	16 bar	GF52.0+CF52.0

Referans Kořullar	İřle :7 bar(g)	alıřma sıca :35'C	ıylenme noktası :+3'C
-------------------	----------------	--------------------	------------------------